


All-dielectric Duct Cables

Cable construction code

UT.x2,3EF xx.yy.zz.c

DIN code

J/A-DQ(ZN)H wbg nx2,3



1. FRP central strength member
2. Water swell-able yarn
3. Gel filled PBT loose tube with optical fibers
4. Water swell-able e-glass yarn
5. Rip-cord
6. FRLSZH UV stable outer jacket

Cable general description

Multi-loose-tube non-metallic cable with standard rodent protection for indoor or outdoor duct installation.

Construction and dimensions	UT6x2,3EF	UT8x2,3EF	UT3x2,3EF	UT9x2,3EF
Max. fibre count (12 fibres/tube)	72	96	144	216
Loose-tubes count	6	8	12	18(6+12) - two layers
Loose tube nominal diameter (mm)	2,3	2,3	2,3	2,3
FRP/coat. CSM nominal thickness (mm)	2,5	2,5/3,9	2,8/6,7	2,5
Outer jacket nominal thickness (mm)	1,2	1,2	1,2	1,2
Cable nominal outer diameter (mm)	10,0	11,4	14,2	14,6
Cable informative weight (kg/km)	100	130	190	195
Standard put-up length (m)	2100/4100 ± 5%	2100/4100 ± 5%	2100/4100 ± 5%	2100/4100 ± 5%

Outer jacket

Material	UV stable FRLSZH
Jacket colour	Black. Other colours available on request
Sheath marking	Ink-Jet, white or black depending on the jacket colour
Print legend	Trademark, construction name, cable type, batch-number, meter-marking, CE marking Customer print legend available on request

Optical fibers

Colour coding (IEC 60304)	1.-12.: red, green, blue, yellow, white, grey, brown, violet, turquoise, black, orange, pink
Loose-tube colour coding	1.red, 2.green (in each layer), rest of tubes white (fillers uncoloured or black)
Fiber type	Single- and multi-mode fibers (OS2, OM1, OM2, OM3, OM4)

Geometrical and transmission parameters are available at separate generic datasheet

All-dielectric Duct Cables

Mechanical characteristics

Test	Test method	Value				Acceptance criteria*	
		UT6x	UT8x	UT3x	UT9x		
Tensile performance	IEC 60794-1-21:E1	long term	800 N	900 N	1000 N	1000 N	$\Delta\alpha \leq 0,05$ dB $\Delta\alpha \leq 0,05$ dB after test
		short term	2000 N	2700 N	3000 N	3000 N	
Crush	IEC 60794-1-21:E3A	1000 N/100mm (long term) 2000 N/100mm (short term)				$\Delta\alpha \leq 0,05$ dB prior release, no damage $\Delta\alpha \leq 0,05$ dB after release, no damage	
Impact	IEC 60794-1-21:E4	10 Nm, 3 impacts, d=20 mm, R=300 mm				$\Delta\alpha \leq 0,05$ dB after test, no damage	
Repeated bending	IEC 60794-1-21:E6	R=20 x cable diameter, 25 cycles				no damage	
Torsion	IEC 60794-1-21:E7	L=1 m, rotation angle $\pm 180^\circ$, 10 cycles				no damage	
Bend	IEC 60794-1-21:E11A	d=20 x cable diameter, 4 turns, 3 cycles				$\Delta\alpha \leq 0,05$ dB after test, no damage	

Environmental characteristic

Test	Test method	Value	Acceptance criteria*
Temperature cycling	IEC 60794-1-22:F1	-40°C ÷ 70°C	$\Delta\alpha \leq 0,05$ dB
Temperature range of use		-5°C ÷ 50°C -40°C ÷ 70°C -40°C ÷ 70°C	installation operation storage, transport
Moisture resistance	IEC 60794-1-22:F5B	L=3 m, 1 m water height, 24 h	no water leakage

* IEC 60794-3-10, IEC 60794-3-11


Cable expected lifetime / min. 30 years

Fire performance

Test	Test method	Result
Flammability - cable bundle	EN 60332-3-22 (cat.A)	Pass
Smoke density	EN 61034-1, EN 61034-2	Pass
Halogen Free, Acid gases	EN 60754-2	Pass
Euro classification to CPR	EN 50575, EN 13501-6	Eca

Order information

Order code e.g.: UT6x2,3EF 06.12.M3.B



Detailed explanation of the FOC constructions coding found in the file *FOC coding*.